

**MarkTime**<sup>®</sup>  
Brand of Energy Saving Products

## In-Wall Series Time Switches

- ☞ Dual switch functionality (select models)
- ☞ LED indicators (select models)
- ☞ Preset time control
- ☞ Incandescent, Fluorescent or CFL Ready
- ☞ Accepts standard decorative wallplate (select models)
- ☞ Energy Saving
- ☞ UL & cUL Approved



**MarkTime<sup>®</sup> In-Wall Time Switches can be found in these applications and more:**



Pools, Saunas,  
Hot Tubs



Bath Fan/Light  
Control



Exterior Lighting



Interior Lighting



# In-Wall Series Time Switches

## Models 42ES1, 42ES2, 42ES2D, 42ES5HD & 42ES624 PIR Sensor Vacancy Switches



- Ideal for lighting control in rooms that are not occupied all the time.
- **42ES2 & 42ES2D** models are 3 way capable using the **42ES4** switch. (Not to be used with fluorescent lamp ballasts.)
- **42ES2D** model has energy saving dimming capability.
- **42ES5HD and 42ES624** heavy duty switches are **fluorescent rated**.
- **42ES1 and 42ES624** models are **California Title 24 Compliant**.
- Hardware items include mounting screws and wire nuts.

Part #	Sensor Area	Manual ON/ Auto OFF	AutoOn/ Auto OFF	Time Setting	Flourescent Rated	CFL Ready	Wall Plate Included	Color	Mode of Activation	Volts	Hz	Watts	Amps	VA	HP	Agency Approval		
42ES1	150° x 10'	x		Up to 30 Min	No	x	x	White or Ivory	Push Button	120	60	1000	15			cULus		
42ES2	150° x 10'		x											500	15			
42ES2D	150° x 10'		x											500	15			
42ES4	No Sensor											x		500	15			
42ES5HD	180° x 10'		x				x					x	x	800			800	1/4
42ES624	180° x 10'	x					x					x	x	500			500	1/8

Use for: Lighting Control in Commercial, Industrial and Residential Applications

## Models 42M24T Electromechanical Time Switch and 42E724P Programmable Electrical Time Switch



- Automatically turns appliances "ON/OFF" on a daily or weekly schedule
- **42M24T** model - Quick setting electromechanical timer with 30-minute increments.
- **42E724P** model - LCD display for easy reading. Slim design with manual override.
- CFL Ready. (Note: Not to be used with fluorescent lamp ballasts.)
- White wall plates included.
- Hardware items include mounting screws and wire nuts.

Part #	Programmable	Reset	AutoOn/ Auto OFF	Time Setting Up To	Flourescent Rated	CFL Ready	Color	Mode of Activation	Switching	Volts	Hz	Amps	HP	Battery Backup	Agency Approval
42E724P	x	Auto	x	10,080 Minutes	No	x	White	Push Button	SPST	120	60	15	1	x	cULus
42M24T	x		x	1440 Minutes				Sliding Tabs				20		No	

Use for: Residential Indoor and Outdoor Lighting, Pool Circulating Pumps, Exhaust/Ceiling Fans and other electrical circuits up to 120V.

## Models 42E20 Electronic Countdown Time Switch



- Ideal as bath fan or light control and other high moisture areas to reduce bacterial and mold growth.
- LED lights indicate proper function and easy locating in darkened areas.
- **42722 and 42723** can be used with fluorescent lamp ballasts.
- Wall plates not included. Use with decorative wall plates.
- Hardware items include captive mounting screws and wire nuts.

Part #	Reset	Auto OFF	Preset Time Range	Flourescent Rated	CFL Ready	Wall Plate	Color	Mode of Activation	Switching	Volts	Hz	Watts	VA	HP	Agency Approval
42722-1	Auto	x	1, 2, 4, 8 Hours	x	x	Not Included	White & Ivory Overlays	Push Button	SPST	120	60	500	200	1/3	cULus
42723-1			15, 30, 60, 120 Minutes												

Use for: Wholehouse and Standard Exhaust Fans

# In-Wall Series Time Switches

## Model 42E02 Electronic and 42000 Series Commercial Grade Electronic Fan/Light Time Switches



- Ideal for removing excess moisture from bath or high moisture areas reducing mold and bacteria growth.
- **42000 Series** - Toggle to down position; light turns "Off", fan remains "On" for pre-set time. (Not to be used with fluorescent lamp ballasts.)
- **Model 42E02** - LED lights indicate proper function. CFL Ready.
- Wall plates not included. **Model 42E02 and 42000 Series** use decorative wall plates.
- Hardware items include captive mounting screws and wire nuts.

Part #	Reset	Auto OFF	Time Setting Up To	Fluorescent Rated	CFL Ready	Color	Mode of Activation	Switching	Volts	Hz	Watts	VA	Hp	Agency Approval
42503	Manual	x	60 Min.	No	No	Ivory	3 Position-Toggle	2 SPST	120	60	500	N/A	1/3	cULus
42507						White	2 Position-Toggle							
42513						Ivory	2 Position-Toggle							
42517						White	2 Position-Toggle							
42702-1 (42E02)	Auto		Preset: 20, 40, 60 Min	x	x	White & Ivory Overlays	2 Position-Push Button				200	1/6		

Use for: Residential, Commercial & Institutional Bathrooms

## 93000 Series Commercial Grade Time Switch



- **93000 Series** is interchangeable with a standard toggle switch to turn circuits either "On" or "Off" at the end of a preset time duration.
- CFL Ready. (Not to be used with fluorescent lamp ballasts.)
- Package includes both white and ivory knobs and decorator dials. Wall plate not included. Use with decorative wall plates.
- Brushed Aluminum wall plate and black knob available.
- Hardware items include captive mounting screws.

Part #	Part # - With Aluminum Plate	Time Setting	Degree of Wind	Hold Option	General Purpose	Flourescent	CFL Ready	Switching	Volts	Hz	Amps (GP)	Amps (Tungsten)	HP	Agency Approval
93501	93301	Up to 15 Minutes	310		x	NOTE: Do NOT use with Flourescent Lamp Ballasts.	x	N.O. & N.C.	125/250	60	20/10	7	1	cULus
93502	93302	Up to 30 Minutes	310		x		x							
93503	93303	Up to 60 Min. (1 Hr.)	310		x		x							
93504	93304	Up to 120 Min. (2 Hr.)	310		x		x							
93505	93306	Up to 360 Min. (6 Hr.)	310		x		x							
93506	93307	Up to 720 Min. (12 Hr.)	310		x		x							
93507	93305	Up to 240 Min. (4 Hr.)	310		x		x							
NA	93311	Up to 15 Minutes	310	x	x		x							
NA	93312	Up to 30 Minutes	310	x	x		x							
93513	93313	Up to 60 Min. (1 Hr.)	310	x	x		x							
93516	93317	Up to 720 Min. (12 Hr.)	310	x	x		x							

Use for: Wholehouse and Commercial Exhaust Fans, Heat Lamps, Whirlpools and Saunas

# In-Wall Series Time Switches

## Model 70AB Heavy Duty Time Switch



74112AB



- **70AB Series** switches are the most robust in-wall time switch in the industry offering a 28 Amp rating.
- Double gang wall box mount.
- Brushed Aluminum wall plate and black knob included. Mounting screws included.

Part #	Time setting	Degree of Wind	Hold Option	General Purpose	Flourescent	CFL Ready	Switching	Volts	Hz	Amps	HP	Agency Approval
72130AB	Up to 60 Min. (1 Hr.)	360		x		x	DPST	240	60	28	1	
72131AB	Up to 60 Min. (1 Hr.)	310	x	x	x							
72132AB	Up to 120 Min. (2 Hr.)	360		x	x							
72134AB	Up to 300 Min. (5 Hr.)	360		x	x							
72136AB	Up to 720 Min. (12 Hr.)	360		x	x							
72137AB	Up to 720 Min. (12 Hr.)	310	x	x	x							
72144AB	Up to 15 Minutes	360		x	x							
72146AB	Up to 30 Minutes	360		x	x							
74112AB	Up to 60 Min. (1 Hr.)	360		x	x							
74113AB	Up to 60 Min. (1 Hr.)	310	x	x	x							
74114AB	Up to 120 Min. (2 Hr.)	360		x	x							
74116AB	Up to 300 Min. (5 Hr.)	360		x	x							
74118AB	Up to 720 Min. (12 Hr.)	360		x	x							
74119AB	Up to 720 Min. (12 Hr.)	310	x	x	x	SPDT						
74122AB	Up to 15 Minutes	360		x	x							
74124AB	Up to 30 Minutes	360		x	x							

NOTE: Do NOT use with Flourescent Lamp Ballasts.

Use for: Pools, Saunas, heavy duty blower control and other circuits requiring a 28 Amp load.

Look to MarkTime® In-Wall Switches and Plug-In Timers for all your Energy Saving Solutions!



Model # 88030  
Programmable Plug-In  
Timer with 2 Outlets



Model # 88P120  
Programmable Plug-In  
Timer with 1 Outlet



Model # 88M1724T  
Mechanical Plug-In  
Timer with Outlet



[www.mrhodes.com](http://www.mrhodes.com)

M.H. Rhodes/Cramer Company  
105 Nutmeg Road South • South Windsor, CT 06074 USA  
TF: 877.684.6464 • PH: 860.291.8402 • FX: 860.620.0897