

## Hydraulic Pumps & Miscellaneous

The professional contractor looks to Greenlee for exceptional bolt cutters, hydraulic pumps, accessories and a variety of rope. Each product is designed to make your job faster, safer and easier – get the job done right with Greenlee. To choose the right tool for your job, contact customer service or see your local Greenlee distributor.

### Contents

|                       |     |
|-----------------------|-----|
| Bolt Cutters          | 428 |
| Hydraulic Pumps       | 430 |
| Accessories           | 433 |
| Touch-up Paint        | 434 |
| Hydraulic Oil         | 434 |
| Rope                  | 434 |
| Cutting/Threading Oil | 435 |



**GREENLEE®**  
A Textron Company

**MADE FOR THE TRADE!™**

## BOLT CUTTERS

### Heavy-Duty Bolt Cutters with Fiberglass Handles



- Unique cam bolt blade adjustment for easy cutter alignment.
- Forged steel blades for long life.
- Clevis-mounted blades for greater strength.
- Custom rubber grips for maximum power.
- Fiberglass handles are tough and lightweight.

#### SPECIFICATIONS

| CAPACITY | RB85*          | RC40*           |
|----------|----------------|-----------------|
| HDFBC18  | 5/16" (7.9 mm) | 7/32" (5.6 mm)  |
| HDFBC24  | 3/8" (9.5 mm)  | 9/32" (7.1 mm)  |
| HDFBC30  | 1/2" (12.7 mm) | 5/16" (7.9 mm)  |
| HDFBC36  | 5/8" (15.9 mm) | 11/32" (8.7 mm) |

\*Indicates bolt hardness in Rockwell units

#### WEIGHT

HDFBC18 – 3.4 lbs. (1.5 kg); HDFBC24 – 10.3 lbs. (4.7 kg)  
HDFBC30 – 4.9 lbs. (2 kg); HDFBC36 – 7.6 lbs. (3.4 kg)

#### CAT. NO. UPC NO. DESCRIPTION

|         |       |  |
|---------|-------|--|
| HDFBC18 | 11277 | Heavy-Duty Bolt Cutter with Fiberglass Handles<br>18 in. (457 mm) Long |
| HDFBC24 | 11278 | Heavy-Duty Bolt Cutter with Fiberglass Handles<br>24 in. (610 mm) Long |
| HDFBC30 | 11279 | Heavy-Duty Bolt Cutter with Fiberglass Handles<br>30 in. (762 mm) Long |
| HDFBC36 | 11280 | Heavy-Duty Bolt Cutter with Fiberglass Handles<br>36 in. (914 mm) Long |
| 11367   | 11367 | Blade Unit for HDFBC18   |
| 11342   | 11342 | Blade Unit for HDFBC24   |
| 11344   | 11344 | Blade Unit for HDFBC30   |
| 11346   | 11346 | Blade Unit for HDFBC36   |

### Heavy-Duty Bolt Cutters



- Unique cam bolt blade adjustment for easy cutter alignment.
- Forged steel blades for long life.
- Clevis-mounted blades for greater strength.
- Custom rubber grips for maximum power.

#### SPECIFICATIONS

| CAPACITY | RB85*          | RC40*           |
|----------|----------------|-----------------|
| HDBC24   | 3/8" (9.5 mm)  | 9/32" (7.1 mm)  |
| HDBC30   | 1/2" (12.7 mm) | 5/16" (7.9 mm)  |
| HDBC36   | 5/8" (15.9 mm) | 11/32" (8.7 mm) |
| HDBC42   | 3/4" (19.1 mm) | 3/8" (9.5 mm)   |

\*Indicates bolt hardness in Rockwell units

#### WEIGHT

HDBC24 – 5.8 lbs. (2.6 kg); HDBC30 – 8.9 lbs. (4 kg);  
HDBC36 – 13.3 lbs. (6 kg); HDBC42 – 19.8 lbs. (9 kg)

#### CAT. NO. UPC NO. DESCRIPTION

|        |       |  |
|--------|-------|--|
| HDBC24 | 11273 | Heavy-Duty Bolt Cutter - 24 in. (610 mm) Long  |
| HDBC30 | 11274 | Heavy-Duty Bolt Cutter - 30 in. (762 mm) Long  |
| HDBC36 | 11275 | Heavy-Duty Bolt Cutter - 36 in. (914 mm) Long  |
| HDBC42 | 11276 | Heavy-Duty Bolt Cutter - 42 in. (1067 mm) Long |
| 11342  | 11342 | Blade Unit for HDBC24                          |
| 11344  | 11344 | Blade Unit for HDBC30                          |
| 11346  | 11346 | Blade Unit for HDBC36                          |
| 11348  | 11348 | Blade Unit for HDBC42                          |

## Bolt Cutters



### SPECIFICATIONS

| CAPACITY | RB85*          | RC40*           |
|----------|----------------|-----------------|
| BC14     | 1/4" (6.4 mm)  | 3/16" (4.8 mm)  |
| BC18     | 5/16" (7.9 mm) | 1/4" (6.4 mm)   |
| BC24     | 3/8" (9.5 mm)  | 5/16" (7.9 mm)  |
| BC30     | 1/2" (12.7 mm) | 11/32" (8.7 mm) |
| BC36     | 5/8" (15.9 mm) | 3/8" (9.5 mm)   |

\*Indicates bolt hardness in Rockwell units

### WEIGHT

BC14 – 2.4 lbs. (1.1 kg); BC18 – 3.4 lbs. (1.5 kg);  
BC24 – 5.8 lbs. (2.6 kg); BC30 – 8.9 lbs. (4 kg);  
BC36 – 13.3 lbs. (6 kg)

- Unique cam bolt blade adjustment for easy cutter alignment.
- Forged steel blades for long life.
- Clevis-mounted blades for greater strength.
- Custom rubber grips for maximum power.

| CAT. NO. | UPC NO. | DESCRIPTION                                 |
|----------|---------|---|
| BC14     | 11267   | Standard Bolt Cutter - 14 in. (356 mm) Long |
| BC18     | 11268   | Standard Bolt Cutter - 18 in. (457 mm) Long |
| BC24     | 11269   | Standard Bolt Cutter - 24 in. (610 mm) Long |
| BC30     | 11270   | Standard Bolt Cutter - 30 in. (762 mm) Long |
| BC36     | 11271   | Standard Bolt Cutter - 36 in. (914 mm) Long |
| 11281    | 11281   | R Blade Unit for BC14                       |
| 11301    | 11301   | R Blade Unit for BC18                       |
| 11306    | 11306   | R Blade Unit for BC24                       |
| 11316    | 11316   | R Blade Unit for BC30                       |
| 11321    | 11321   | R Blade Unit for BC36                       |

## Threaded Rod Cutter



### SPECIFICATIONS

|                 |   |
|-----------------|---|
| <b>Capacity</b> | 1/4" - 20 soft steel rod (6.4 mm);<br>3/8" - 16 soft steel rod (9.5 mm) |
| <b>Weight</b>   | 14.1 lbs. (6.4 kg)  |

- One stroke cuts through threaded rod.
- Cuts clean, eliminating the need to grind or file before threading a nut onto cut end.
- Wide base for stable cutting. Includes mounting hole for fast and easy permanent mounting to work surface.
- Strong forged steel cutting head with tool steel cutting die for long life.
- Includes: Threaded Rod Cutter, 1/4" - 20 Cutting Die Set, 3/8" - 16 Cutting Die Set.

| CAT. NO. | UPC NO. | DESCRIPTION               |
|----------|---------|---------------------------|
| 36587    | 36587   | Threaded Rod Cutter       |
| 37186    | 37186   | 1/4" - 20 Cutting Die Set |
| 37187    | 37187   | 3/8" - 16 Cutting Die Set |



## HYDRAULIC PUMPS

### High-Pressure Hydraulic Hand Pump



- Portable and powerful, for use with Greenlee Benders.
- Versatile, operates in any position.
- Steel pump body and handle with rubber grip.
- Wide base for stability.
- Mounting holes for permanent positioning.
- Includes 3/8" (9.5 mm) female hydraulic connector and dust cap.

#### SPECIFICATIONS

|                  |  |
|------------------|--|
| <b>Operation</b> | Manual – Hand                                      |
| <b>Capacity</b>  | 10,000 psi (700 bar), .161 in. (26 mm.) per stroke |
| <b>Length</b>    | 25-1/2" (648 mm)                                   |
| <b>Width</b>     | 7" (178 mm)  |
| <b>Height</b>    | 6" (152 mm)  |

NOTE: See page 433 to select the proper hydraulic hose for this pump.

| CAT. NO. | UPC NO. | DESCRIPTION                       | WEIGHT |     |
|----------|---------|-----------------------------------|--------|-----|
|          |         |                                   | LBS.   | kg  |
| 755      | 15677   | High-Pressure Hydraulic Hand Pump | 18     | 8.2 |
| 18272    | 18272   | <b>R</b> Seal Kit                 |        |     |

### Hydraulic Hand Pump



- Lightweight and portable, for use with Greenlee Punch Drivers.
- Versatile, operates in any position.
- Single speed.
- Rugged steel pump body/reservoir with cast aluminum handle.
- Has mounting holes for easy, permanent mounting.

| CAT. NO. | UPC NO. | DESCRIPTION   | WEIGHT |     |
|----------|---------|---|--------|-----|
|          |         |   | LBS.   | kg  |
| 767      | 13284   | Hydraulic Hand Pump   | 6      | 2.7 |
| 04343    | 04343   | <b>R</b> Seal Kit Repair for Serial Code ABM                                |        |     |
| 13800    | 13800   | <b>R</b> *Seal Kit Repair for Serial Code 55D & Up                          |        |     |
| 30242    | 30242   | <b>R</b> *Seal Kit Repair for Serial Code 68BG TO BG33181628, BG331816 & Up |        |     |
| 30241    | 30241   | <b>R</b> Reservoir Follower   |        |     |

\*NOTE: Must also purchase 30241 Follower

#### SPECIFICATIONS

|                  |  |
|------------------|--|
| <b>Operation</b> | Manual – Hand                                      |
| <b>Capacity</b>  | 6,500 psi (448 bar), .0823 in. (13 mm.) per stroke |
| <b>Length</b>    | 13" (330 mm)                                       |
| <b>Width</b>     | 4" (102 mm)  |
| <b>Height</b>    | 4" (102 mm)  |

NOTE: See page 433 to select the proper hydraulic hose for this pump.

## Hydraulic Foot Pump



- Free both hands to position and hold the working tool.
- Foot activated release lever.
- Hold-down pin keeps pedal down for storage and transport.
- Angled base bar keeps the pump upright and stable.
- Includes 1/4" (6.4 mm) female coupler with dust cap.

| CAT. NO. | UPC NO. | DESCRIPTION                         | WEIGHT |    |
|----------|---------|-------------------------------------|--------|----|
|          |         |                                     | LBS.   | kg |
| 1725     | 31353   | Hydraulic Foot Pump                 | 11     | 5  |
| 24496    | 24496   | <b>R</b> Seal Kit w/ RD Serial Code |        |    |
| 25214    | 25214   | <b>R</b> Seal Kit w/ RU Serial Code |        |    |
| 33336    | 33336   | <b>R</b> Seal Kit w/ VK Serial Code |        |    |

### SPECIFICATIONS

|                  |  |
|------------------|--|
| <b>Operation</b> | Manual – Foot  |
| <b>Capacity</b>  | 6,500 psi (448 bar), .117 in <sub>3</sub> (19 mm <sub>3</sub> ) per stroke |
| <b>Length</b>    | 16" (406 mm)   |
| <b>Height</b>    | Pedal down 6" (152 mm), Pedal up 12" (305 mm)                              |
| <b>Width</b>     | 8" (203 mm)  |

NOTE: See page 433 to select the proper hydraulic hose for this pump.

## Hand-Operated Hydraulic Pump



- Two-speed hydraulic pump. Ideal for use with remote cutting and crimping tools.
- Compact and lightweight – easy to move around jobsites.
- Solid base with wide legs provides for good stability during operation.
- Built-in carrying handle.
- Large, easy-to-grasp, retraction wheel.
- Equipped with 3/8" female screw-type hydraulic coupler.

| CAT. NO. | UPC NO. | DESCRIPTION                  | WEIGHT |     |
|----------|---------|------------------------------|--------|-----|
|          |         |                              | LBS.   | kg  |
| 7475H    | 07475   | Hand-Operated Hydraulic Pump | 18     | 8.2 |
| 07829    | 07829   | <b>R</b> Seal Kit            |        |     |

### SPECIFICATIONS

|  |                         |
|--|-------------------------|
| <b>Max output pressure</b>               | 10,000 psi (700 bar)    |
| <b>Useable oil capacity</b>              | 0.75 quart (0.74 liter) |
| <b>1st stage oil volume (200 psi)</b>    | 0.82 cu in/stroke       |
| <b>2nd stage oil volume (10,000 psi)</b> | 0.16 cu in/stroke       |
| <b>Length (including coupler)</b>        | 25" (635 mm)            |
| <b>Width</b>                             | 5-5/8" (143 mm)         |
| <b>Height</b>                            | 5-1/2" (140 mm)         |

NOTE: See page 433 to select the proper hydraulic hose for this pump.

## Electric Hydraulic Pump



- Useable oil volume: 3 quarts (2.8 liters).
- For use with Greenlee 2" capacity benders.
- Automatic or manual ram-return selector valve provides more control from the pendant switch.
- Molded enclosure protects pump, motor and circuitry in tough working environments.
- Use with single-hose hydraulic systems with spring-return rams.

| CAT. NO. | UPC NO. | DESCRIPTION             | WEIGHT |    |
|----------|---------|-------------------------|--------|----|
|          |         |                         | LBS.   | kg |
| 975      | 33516   | Electric Hydraulic Pump | 51     | 23 |
| 34369    | 34369   | <b>R</b> Seal Kit       |        |    |

### SPECIFICATIONS

|                  |  |
|------------------|--|
| <b>Operation</b> | 120 VAC 1/2 HP (.375 kW)   |
| <b>Capacity</b>  | 10,000 psi (700 bar); 250 in <sub>3</sub> (4 L) per minute rapid advance; 18 in <sub>3</sub> (.32 L) per minute at full pressure |
| <b>Length</b>    | 12" (305 mm)   |
| <b>Width</b>     | 10" (254 mm)   |
| <b>Height</b>    | 15-1/2" (394 mm)   |

NOTE: See page 433 to select the proper hydraulic hose for this pump.

## Electric Hydraulic Pump



- Useable oil volume: 6-1/4 quarts (5.9 liters)
- For use with all Greenlee benders.
- Solid state controls for added reliability.
- Low pressure for fast ram advance, automatically changes to low volume high pressure.
- Pendant control for advance, valve on pump for release.
- Use with single-hose hydraulic systems with spring-return rams.
- Equipped with four swivel casters.
- Cast aluminum reservoir for long life.

| CAT. NO. | UPC NO. | DESCRIPTION             | WEIGHT |    |
|----------|---------|-------------------------|--------|----|
|          |         |                         | LBS.   | kg |
| 960 SAPS | 18297   | Electric Hydraulic Pump | 92     | 42 |
| 18416    | 18416   | Ⓡ Seal Kit              |        |    |

### SPECIFICATIONS

|                  |   |
|------------------|---|
| <b>Operation</b> | 120 VAC 1-1/2 HP (1.12 kW)  |
| <b>Capacity</b>  | 10,000 psi (700 bar); 300 inch, (4.8 L) per minute rapid advance; 54 inch, (.9 L) per minute at full pressure |
| <b>Length</b>    | 12" (305 mm)  |
| <b>Width</b>     | 10-3/4" (223 mm)  |
| <b>Height</b>    | 22-5/16" (567 mm)   |

NOTE: See page 433 to select the proper hydraulic hose for this pump.

## Electric Hydraulic Pump



- Useable oil volume: 6 quarts (5.7 liters).
- For use with all Greenlee benders.
- Handy pendant advance control on 980 and 980-22PS.
- Low voltage pendant coupled to solid state motor controls eliminates contact arcing for greater reliability and longer life.
- Automatic or manual ram return selector valve provides more control from the pendant switch.
- Molded enclosure protects pump, motor and circuitry in tough working environments.
- Use with single-hose hydraulic systems with spring-return rams.

| CAT. NO. | UPC NO. | DESCRIPTION                                 | WEIGHT |    |
|----------|---------|---|--------|----|
|          |         |   | LBS.   | kg |
| 980      | 33515   | Electric Hydraulic Pump with Pendant        | 71     | 32 |
| 980-22   | 36314   | Electric Hydraulic Pump                     | 71     | 32 |
| 980-22PS | 36313   | Electric Hydraulic Pump with Pendant Switch | 71     | 32 |
| 34369    | 34369   | Ⓡ Seal Kit                                  |        |    |

Note: 980-22 is 220V pump only, no control switch

### SPECIFICATIONS

|                  |   |
|------------------|---|
| <b>Operation</b> | 980 – 120 VAC 1-1/2 Hp (1.12 kW)<br>980-22PS – 220 VAC 50Hz 1-1/2 Hp (1.12 kW)                              |
| <b>Capacity</b>  | 10,000 psi (700 bar); 250 inch, (4 L) per minute rapid advance; 54 inch, (.9 L) per minute at full pressure |
| <b>Length</b>    | 12" (305 mm)  |
| <b>Width</b>     | 12" (305 mm)  |
| <b>Height</b>    | 17-1/2" (445 mm)  |

NOTE: See page 433 to select the proper hydraulic hose for this pump.

# ACCESSORIES

## Hydraulic Hose Selection Guide

| TOOL CAT. NO./DESCRIPTION | TOOL COUPLER        | PUMP CAT. NO.            | HOSE CAT./UPC NO. |
|---------------------------|---------------------|--------------------------|-------------------|
| 750 Cable Cutter          | 1/4" Female Coupler | 767                      | 38316             |
| 750 Cable Cutter          | 1/4" Female Coupler | 1725                     | 37729             |
| 750 Cable Cutter          | 1/4" Female Coupler | 975                      | 17707             |
| 777 Bender                | 3/8" Female Coupler | 755, 975, 980 or 960SAPS | 11289             |
| 782 Bender                | 3/8" Female Coupler | 755 or 975               | 11289             |
| 800 Cable Bender          | 1/4" Female Coupler | 1725                     | 37729             |
| 880 Bender                | 3/8" Female Coupler | 755 or 975               | 11289             |
| 882 Bender                | 3/8" Female Coupler | 755 or 975               | 11289             |
| 884 Bender                | 3/8" Female Coupler | 980 or 960SAPS           | 11289             |
| 885 Bender                | 3/8" Female Coupler | 980 or 960SAPS           | 11289             |
| 1731 C-Frame Punch Driver | 1/4" Female Coupler | 767                      | 38316             |
| 1731 C-Frame Punch Driver | 1/4" Female Coupler | 1725                     | 37729             |
| 1731 C-Frame Punch Driver | 1/4" Female Coupler | 755 or 975               | 11289             |
| SDK202GL Cable Cutter     | 3/8" Male Coupler   | 7475H, 975 or 980        | 05850, 05851      |
| RK06AT, RK06FT            | 3/8" Male Coupler   | 7475H, 975 or 980        | 05850, 05851      |
| RK1230, RK1240, RK1240K   | 3/8" Male Coupler   | 7475H, 975 or 980        | 05850, 05851      |
| RCCX                      | 3/8" Male Coupler   | 7475H, 975 or 980        | 05850, 05851      |
| RK1550                    | 3/8" Male Coupler   | 7475H, 975 or 980        | 05850, 05851      |

## Hydraulic Hose Units



- High pressure hydraulic hose units for use with Greenlee hydraulic pumps.
- Equipped with couplers and dust caps.

| CAT. NO. | UPC NO. | DESCRIPTION   |
|----------|---------|---|
| 05850*   | 05850   | 10' X 1/4" Hose With (1) 3/8" Male Coupler and (1) 3/8" Female Coupler                          |
| 05851*   | 05851   | 10' X 1/4" Non-Conductive Hose with (1) 3/8" Male Coupler and (1) 3/8" Female Coupler           |
| 11289*   | 11289   | 6' X 3/8" Hose with (2) 3/8" Male Couplers  |
| 17707*   | 17707   | 10' X 1/4" Hose with (1) 3/8" Male Coupler and (1) 1/4" Male Coupler                            |
| 37729*   | 37729   | 10' X 1/4" Hose with (2) 1/4" Male Couplers   |
| 38316    | 38316   | 3' X 1/4" Hose with (1) 1/4" Male Coupler and (1) 1/4" NPT Swivel Threaded Fitting              |
| 06302    | 06302   | 3' X 1/4" Hose with (1) 1/4" NPT Male Threaded Fitting and (1) 1/4" NPT Swivel Threaded Fitting |

\* Filled with hydraulic oil.

| CAT. NO. | UPC NO. | DESCRIPTION                                     | HOSE UNIT CAT./UPC NO. |       |       |       |       |       | COUPLER SET CAT./UPC NO. |                  |
|----------|---------|---|------------------------|-------|-------|-------|-------|-------|--------------------------|------------------|
|          |         |   | 05850                  | 05851 | 11289 | 17707 | 37729 | 38316 | 37614                    | 3548GB/<br>20573 |
| 54167    | 54167   | 1/4" (6.4 mm) Female Coupler without Dust Cap   |                        |       |       |       |       |       | 1                        |                  |
| 54168    | 54168   | 1/4" (6.4mm) Dust Cap for Female Coupler        |                        |       |       |       |       |       | 1                        |                  |
| 54169    | 54169   | 1/4" (6.4 mm) Male Coupler without Dust Cap     |                        |       |       | 1     | 2     | 1     | 1                        |                  |
| 54170    | 54170   | 1/4" (6.4 mm) Dust Cap for Male Coupler         |                        |       |       | 1     | 2     | 1     | 1                        |                  |
| 4018GB   | 50807   | 3/8" (9.6 mm) Female Coupler with Dust Cap      |                        |       |       |       |       |       |                          | 1                |
| 4033GB   | 50823   | 3/8" (9.6 mm) Male Coupler with Dust Cap        |                        |       | 2     | 1     |       |       |                          | 1                |
| 41877    | 41877   | 3/8" (9.6 mm) Female Coupler without Dust Cap   | 1                      | 1     |       |       |       |       |                          |                  |
| 41941    | 41941   | 3/8" (9.6 mm) Male Coupler without Dust Cap     | 1                      | 1     |       |       |       |       |                          |                  |
| 41834    | 41834   | 3/8" (9.6 mm) Dust Cap for 41941/41877 Couplers | 2                      | 2     |       |       |       |       |                          |                  |



## Greenlee Green Spray Touch-up Paint



- Closely matches Greenlee painted products.

| CAT. NO. | UPC NO. | DESCRIPTION   | WEIGHT |    |
|----------|---------|---|--------|----|
|          |         |   | LBS.   | kg |
| 22618    | 22618   | 13 oz. (384 ml) Aerosol Can of Greenlee Green Spray Paint       | 1.2    | .5 |
| 10378    | 10378   | 13 oz. (384 ml) Aerosol Can of Greenlee Flat Green Spray Paint* | 1.2    | .5 |

NOTE: The color green is a registered trademark for Test Instruments, Job Boxes, Benders and Pulling Equipment.  
\*Storage Box

## Hydraulic Oil



- Greenlee-approved hydraulic oil.
- Specially compounded for use with Greenlee hydraulic equipment.
- Refinery-filtered to give you the finest oil available.

| CAT. NO. | UPC NO. | DESCRIPTION                      | WEIGHT |      |
|----------|---------|----------------------------------|--------|------|
|          |         |                                  | LBS.   | kg   |
| 4016 GB  | 51059   | Hydraulic Oil – 1 Gallon (3.8 l) | 8.5    | 3.9  |
| 4017 GB  | 50806   | Hydraulic Oil – 1 Quart (.9 l)   | 2.25   | 1.02 |

NOTE: For best operation of your Greenlee hydraulic-powered equipment, use Greenlee hydraulic oil only. (Do not use hydraulic brake fluid, shock absorber fluid, alcohol, glycerine, castor oil or other non-specified fluid—as they reduce performance and can cause damage to pumps and equipment.) Use of improper fluids waives the guarantee on Greenlee hydraulic equipment.

## Polypro General Purpose Rope



405 Rope Stand sold separately. See page 165.

- **Not for cable pulling.** See the ropes listed with cable pullers for recommended cable pulling ropes.
- Highly-visible, bright yellow with green tracer, excellent for roping off areas on construction sites.
- Rot and mildew resistant.
- Weather resistant.
- Economical general purpose rope.



| ROPE LENGTH              | CAT. NO.     | UPC NO. | BREAKING STRENGTH | AVERAGE WEIGHT |      |
|--------------------------|--------------|---------|-------------------|----------------|------|
|                          |              |         |                   | LBS.           | kg.  |
| <b>3/16"</b><br>(4.8 mm) | 250' 76 m    | 408     | 720 lbs. 3.2 kN   | 3              | 1.4  |
|                          | 600' 182 m   | 409     | 720 lbs. 3.2 kN   | 6              | 2.7  |
| <b>1/4"</b><br>(6.4 mm)  | 250' 76 m    | 412     | 1130 lbs. 5.0 kN  | 4              | 1.8  |
|                          | 600' 182 m   | 413     | 1130 lbs. 5.0 kN  | 9              | 4.1  |
|                          | 1,000' 304 m | 414     | 1130 lbs. 5.0 kN  | 13             | 5.9  |
| <b>3/8"</b><br>(9.5 mm)  | 250' 76 m    | 417     | 2430 lbs. 10.8 kN | 9              | 4.1  |
|                          | 600' 182 m   | 418     | 2430 lbs. 10.8 kN | 19             | 8.6  |
| <b>1/2"</b><br>(12.7 mm) | 250' 76 m    | 421     | 3780 lbs. 16.8 kN | 15             | 6.8  |
|                          | 600' 182 m   | 422     | 3780 lbs. 16.8 kN | 35             | 15.9 |



## Chain-Type Pipe Vice



- Use with a wide range of sizes of pipe or conduit.
- Built-in pipe rest.
- To prevent marring of plastic or plastic coated pipe, vise jaws can be rotated with smooth side up. Use serrated side for harder materials.
- Chain design holds pipe securely to prevent it from twisting or turning during threading.

| CAT. NO. | UPC NO. | DESCRIPTION          |
|----------|---------|----------------------|
| 467      | 27318   | Chain-Type Pipe Vise |

### SPECIFICATIONS

|                 |                                  |
|-----------------|----------------------------------|
| <b>Capacity</b> | 1/8" - 5" (3.2 mm x 127 mm) pipe |
| <b>Weight</b>   | 17 lbs. (7.7 kg)                 |

## Cutting/Threading Oil



- Premium quality, high lubricity for easier cutting and long tool life.
- Choice of light or dark.

| CAT. NO. | UPC NO. | DESCRIPTION                         |
|----------|---------|-------------------------------------|
| 462B     | 11412   | Dark Cutting/Threading Oil - 1 Pt.  |
| 462-Q    | 28237   | Dark Cutting/Threading Oil - 1 Qt.  |
| 462-1    | 26096   | Dark Cutting/Threading Oil - 1Gal   |
| 463-Q    | 28238   | Light Cutting/Threading Oil - 1 Qt  |
| 463-1    | 28239   | Light Cutting/Threading Oil - 1 Gal |

### SPECIFICATIONS

| CAT. NO.     | SIZE           | WEIGHT          |
|--------------|----------------|-----------------|
| 462-Q, 463-Q | 1 Qt. (.9 l)   | 2.3 lbs. (1 kg) |
| 462-1, 463-1 | 1 Gal. (3.8 l) | 8.7 lbs. (4 kg) |



## NOTES

### Hydraulic Pumps & Miscellaneous

#### INTERNATIONAL

Tel: +1.815.397.7070  
Fax: +1.815.397.9247

#### CANADA

Tel: 800.435.0786  
Fax: 800.524.2853

#### USA

Tel: 800.435.0786  
Fax: 800.451.2632