








# Selector Guide

<b>Cube Timers</b>				
Series	RLY210	RLY220	RLY230	RLY240
				
<b>Features</b>	<ul style="list-style-type: none"> <li>• Delay On Operate</li> <li>• Solid State</li> <li>• Industry Standard Package</li> <li>• Transient Protected</li> <li>• .250" Quick Connect Terminals</li> </ul>	<ul style="list-style-type: none"> <li>• Delay On Operate</li> <li>• Solid State</li> <li>• Industry Standard Package</li> <li>• Transient Protected</li> <li>• .250" Quick Connect Terminals</li> </ul>	<ul style="list-style-type: none"> <li>• Delay On Operate</li> <li>• 0.1% Repeat Accuracy</li> <li>• Solid State</li> <li>• Industry Standard Package</li> <li>• .250" Quick Connect Terminals</li> </ul>	<ul style="list-style-type: none"> <li>• Interval ON</li> <li>• Solid State</li> <li>• Industry Standard Package</li> <li>• Transient Protected</li> <li>• .250" Quick Connect Terminals</li> </ul>
<b>Time Delay Selection Method</b>	External Resistor Adjustable	Knob Adjustable	Binary Switch Programmable	Knob Adjustable
<b>Switch Configuration</b>	Solid State SPST	Solid State SPST	Solid State SPST	Solid State SPST
<b>Switch Current</b>	40mA – 1A	40mA – 1A	20mA – 1A	40mA – 1A
<b>Operating Vltg Range</b>	19–288VDC/AC 50/60Hz	19–288VDC/AC 50/60Hz	95–145VAC 50/60Hz	19–288VDC/AC 50/60Hz
<b>Timing Adj Range</b>	2 to 600sec	1 to 1000sec	1 to 1023sec	0.2 to 8min.
<b>Page</b>	87	88	89	90

<b>Cube Timers (Cont'd)</b>			
Series	RLY250	RLY260	RLY270
			
<b>Features</b>	<ul style="list-style-type: none"> <li>• Delay On Release</li> <li>• Solid State</li> <li>• Industry Standard Package</li> <li>• Transient Protected</li> <li>• .250" Quick Connect Terminals</li> </ul>	<ul style="list-style-type: none"> <li>• Delay On Operate</li> <li>• High Power</li> <li>• No Heat Sink Required</li> <li>• Transient Protected</li> <li>• .250" Quick Connect Terminals</li> </ul>	<ul style="list-style-type: none"> <li>• One Shot</li> <li>• Interval Timer</li> <li>• High Power</li> <li>• Transient Protected</li> <li>• .250" Quick Connect Terminals</li> </ul>
<b>Time Delay Selection Method</b>	Knob Adjustable	Knob Adjustable	Knob Adjustable
<b>Switch Configuration</b>	Solid State SPST	SPST	SPST
<b>Switch Current</b>	40mA – 1A	500mA – 30A	500mA – 30A
<b>Operating Vltg Range</b>	19–288VAC 50/60Hz	120VAC ±20% 12VDC ±20%	120VAC ±20% 12VDC ±20%
<b>Timing Adj Range</b>	0.1 to 5min	0.3 to 10min	0.3 to 10min
<b>Page</b>	91	92	93